



An Oshkosh Corporation Business

# TELESCOPIC CRANES

## QUICK REFERENCE GUIDE

	Model	Max. Lift Capacity	Rating	Weight	Max. Horizontal Reach*	Max. Vertical Reach**	Extension	Rotation	Required Mounting Space	Min. GVWR***
Electric	3300e-18	3,300 LB	18,000 FT-LB	821 LB	17' - 1"	18' - 1"	2 Hydraulic	400°	17.4" x 16.7"	11,500 LB
	4300e-18	4,000 LB	20,000 FT-LB	821 LB	17' - 1"	18' - 1"	2 Hydraulic	400°	17.4" x 16.7"	15,000 LB
	5300e-23	5,300 LB	32,000 FT-LB	1,231 LB	22' - 2"	23' - 4"	2 Hydraulic	400°	19.9" x 17.3"	18,000 LB
	6300e-23	6,300 LB	47,000 FT-LB	1,231 LB	22' - 2"	23' - 4"	2 Hydraulic	400°	19.9" x 17.3"	18,000 LB
Hydraulic	3300-18	3,300 LB	18,000 FT-LB	771 LB	17' - 1"	18' - 1"	2 Hydraulic	400°	17.4" x 16.7"	11,500 LB
	4300-18	4,000 LB	20,000 FT-LB	771 LB	17' - 1"	18' - 1"	2 Hydraulic	400°	17.4" x 16.7"	15,000 LB
	5300-23	5,300 LB	32,000 FT-LB	1,181 LB	22' - 2"	23' - 4"	2 Hydraulic	400°	19.9" x 17.3"	18,000 LB
	6300-23	6,300 LB	47,000 FT-LB	1,181 LB	22' - 2"	23' - 4"	2 Hydraulic	400°	19.9" x 17.3"	18,000 LB
	7600-27	7,600 LB	50,000 FT-LB	1,697 LB	26' - 3"	27' - 7"	2 Hydraulic	400°	21" x 18"	19,500 LB
	7600-32	7,600 LB	49,000 FT-LB	1,826 LB	30' - 10"	32' - 2"	2 Hydraulic	400°	21" x 18"	19,500 LB
	8600-27	8,600 LB	55,000 FT-LB	1,697 LB	26' - 3"	27' - 7"	2 Hydraulic	400°	21" x 18"	19,500 LB
	8600-32	8,600 LB	51,000 FT-LB	1,826 LB	30' - 10"	32' - 2"	2 Hydraulic	400°	21" x 18"	19,500 LB
	10600-27	10,600 LB	79,000 FT-LB	2,117 LB	26' - 1"	27' - 5"	2 Hydraulic	400°	22" x 19"	26,000 LB
	10600-32	10,600 LB	77,000 FT-LB	2,286 LB	30' - 11"	32' - 2"	2 Hydraulic	400°	22" x 19"	26,000 LB
	12600-27	12,600 LB	96,000 FT-LB	2,117 LB	26' - 1"	27' - 5"	2 Hydraulic	400°	22" x 19"	26,000 LB
	12600-32	12,600 LB	90,000 FT-LB	2,286 LB	30' - 11"	32' - 2"	2 Hydraulic	400°	22" x 19"	26,000 LB
	14000-25	14,000 LB	95,000 FT-LB	3,100 LB	24' - 10"	26' - 3"	2 Hydraulic	400°	24" x 25"	33,000 LB
	14000-30	14,000 LB	94,000 FT-LB	3,280 LB	30' - 11"	32' - 3"	2 Hydraulic	400°	24" x 25"	33,000 LB

\*Flip sheave up & single line (From centerline of rotation)

\*\* From mounting surface

\*\*\*The gross vehicle weight rating (GVWR) is a minimum guideline. Contact IMT if you have questions regarding your particular installation.

IMT reserves the right to make changes in engineering, design, and specifications; add improvements, or discontinue manufacturing at any time without notice or obligation. ©2025 Iowa Mold Tooling Co., Inc. All Rights Reserved.



IMT.com